

# Eco Solvent Printer

1.8m F1080/i3200 Printhead

1.8米 爱普生 F1080/i3200 户内外写真机

Dual Heads	双喷头
4/6 Color	4/6色写真
Variable Dot	可变墨滴
3-Stage Heater	三段加热

3 Print-head Configurations Available  
提供三种喷头配置




## ● Features 特点



### Different Printhead Available

Equipped Epson F1080 or i3200 Head. 4 colors and 6 colors models are optional.


根据你的需求来选择4色或者6色输出



### Heating and Drying System

Front and middle and rear heating system and front drying fan are standard equipped to help dry the printed material fast.

标配前中后加热系统和前置冷却风扇



### Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.


标配防撞装置, 支持中断处续打



### Branded parts

Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.

极大提升设备使用寿命和稳定性



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes.

使打印画面的颜色过渡更加自然, 实现高质量成像

★ New look has heavier, larger structure, and wider printing platform

新造型更加厚重大气, 更宽的打印平台

★ Aluminous carriage girder ensures high accuracy of carriage movement

铝制小车梁, 精度有保障

★ Dual feeding bar for loading heavy media

双送纸杆, 以承受更重的耗材

★ Optional infrared heater for drying prints quickly

选配红外加热装置, 画面极速烘干

★ Integrated temperature controller

一体式温控仪



## ● Specification 参数

Model No.	型号	SJ-740S	SJ-740i	SJ-740E
Printhead	喷头	2×Epson i3200	1×Epson i3200	2×Epson F1080
Resolution	精度	2400dpi max	2400dpi max	1440dpi max
Ink Color	色彩	CMYK	CMYK	CMYK / CMYK Lc Lm
Media 耗材	Size 尺寸	1.8 meter		
	Types 种类	Flex Banner, Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc. 灯箱布, 车贴, 单透贴, 条幅布, 玻璃贴膜, 网格布等		
Speed 速度	Draft 标准	42 m <sup>2</sup> /h	25 m <sup>2</sup> /h	24 m <sup>2</sup> /h
	Production 精细	32 m <sup>2</sup> /h	19 m <sup>2</sup> /h	18 m <sup>2</sup> /h
	Quality 照片	24 m <sup>2</sup> /h	14 m <sup>2</sup> /h	13 m <sup>2</sup> /h
Ink Type	墨水	Eco Solvent Ink		
Ink Droplet	墨滴	1.5-21pl variable		
Cleaning	清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头		
Feed & take up	收放布	Automatic Media Feeding (Standard) & Take up System (Optional)		
Environment	环境	Temperature: 20-28°C, Humidity: 40%-60%		
Rip Software	软件	Maintop/ Photoprint		
Interface	接口	USB 3.0		
Power	电源	Machine 50/60HZ, 110 / 220V, 1200W		
Size & Weight	Machine 机器	L3100×W780×H1500 mm / 280 KG		
	Packing 包装	L3210×W1000×H740 mm / 400 KG		

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。