



Ricoh Gen5/Gen6 Printheads

理光Gen5/Gen6喷头

Variable Dot

可变墨滴

Negative Pressure System

负压系统

White & Varnish

白色和光油

RICOH PRINthead UV FLATBED PRINTER

250×130cm



UV Flatbed Printer | FB-2513R & FB-2513Rs

● Features 特点




Ricoh GEN5 & GEN6 Available, meet the demand of different clients.

可以选择理光Gen5或Gen6喷头，满足不同客户的需求。




Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.

配置高级的负压系统。稳定供墨，简化多头设备维护。




Anti-collision system is equipped to protect the printhead and carriage all the time.

贴心防撞系统设计，保护喷头及机架。



Double built-in high-power independent vacuum pump. Guarantee the powerful suction.

内置独立双高功率抽风机，确保吸力强劲。



Built-in media alignment pins, guarantee the quick, simple and high precision media positioning.

内置耗材定位销，保证耗材快速、简单、高精度定位。

- ★ The high precision machine frame ensures perfect print resolution.
- ★ Automatic media height detecting system is equipped, provide great help for setting the proper print height.
- ★ X axis' s gear fixation components are processed with one-time molding technology.
- ★ X axis is equipped with dual guide rail which ensures smooth movement of carriage.
- ★ Y axis is using screw drive transmission mode.



● Specification 参数

Model No.		型号	FB-2513R	FB-2513Rs
Printhead	喷头	Ricoh Gen5	Ricoh Gen6	
Number of Printheads	数量	2/3/4/5/6/8 pcs optional		
Resolution	精度	Max 1440 dpi		
Media 耗材	Thickness 厚度	Max 12 cm		
	Size 尺寸	2500 × 1300 mm		
	Types 种类	Glass, Acrylic, Ceramic, Metal, Paper, Wood, Leather, PVC , PP, PE, PTFE Etc.		
Speed 速度	Draft 草图	14 sqm/h (CMYK + W , 3 Heads)	17 sqm/h (CMYK + W , 3 Heads)	
	Production 标准	10 sqm/h (CMYK + W , 3 Heads)	12 sqm/h (CMYK + W , 3 Heads)	
	Quality 精细	8 sqm/h (CMYK + W , 3 Heads)	10 sqm/h (CMYK + W , 3 Heads)	
Ink 墨水	Type 墨水	UV Ink		
	Color 颜色	CMYK/CMYK + W/CMYK + W + V		
	Capacity 墨瓶	500 ml		
	Dry System 干燥	UV-LED Light System		
PC Operation System		系统	Windows 7/XP/10	
Environment		环境	Temperature: 20-28°C, Humidity: 40%-60%	
Rip Software		软件	Maintop (Standard) / Photoprint (Optional)	
Image Format		图片格式	TIFF, JPEG, EPS, PDF...	
Power		电源	Max 3.6KW, AC 50/60Hz, 220V(±10%)>12A	
Size 尺寸	Machine 机器	L4120 × W2000 × H1400 mm		
	Packing 包装	L4220 × W2100 × H1610 mm		
Weight 重量	Machine 机器	850 KG		
	Packing 包装	1000 KG		

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。