

Epson Series UV Roll to Roll Printer

UV卷材打印机 — 高性价比之选

Dual Heads

双喷头

4/5-Color

4/5色写真

Variable Dot

可变墨滴

White Optional

白色可选

Epson Official Supplied i1600-U Printheads

配备爱普生官方原装i1600-U喷头



PRECISIONCORE
PRINTHEAD
powered by EPSON

● Features 特点



Epson Officially Supplied Printhead
Equipped Epson i1600-U Head.

4 colors and 5 colors models are optional


根据你的需求来选择4色或者5色输出



Water Cooling UV-LED Lamp

It is one of the world's top UV-LED, long lifespan, low heat, and instant on-off


装备世界顶级的UV-LED, 寿命长, 发热低, 即时开关



Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes

使打印画面的颜色过渡更加自然, 实现高质量成像



Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time

标配防撞装置, 支持中断处续打



Integrated Take Up System

It offers adjustable roll widths, making it suitable for various sized media rolls and applications

卷幅宽度可调, 适用于众多尺寸的卷材

★ High-density UV curable ink produces rich, vibrant colors on coated or uncoated media
高品质UV固化墨水在涂层或非涂层材料上实现丰富而鲜明的色彩

★ Durable, scratch-resistant and virtually odorless, Up to three years outdoor durability without lamination
画面持久, 耐刮擦, 无异味, 不覆膜长达三年的户外耐候性

★ Branded parts are used for high attrition area.
Greatly increased the lifetime and stability of the machine.
For example, Hiwin guide rail, German Iigus drag chain, Italian Megadyne belt

高损耗处皆使用高等级配件, 极大提升设备使用寿命和稳定性



● Specification 参数

Model No.	型号	UV-740D
Printing Head	喷头	2 × Epson i1600-U
Resolution	精度	2400 dpi MAX
Media 耗材	Width 宽度	1800 mm MAX
	Type 种类	Canvas, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc.
Ink 墨水	Type 类型	UV Ink
	Color 颜色	CMYK / CMYK+W
	Curing 固化	High Quality Whater Cooling UV-LED Lamp
Speed 速度	Printing Mode 模式	Color Mode
	Draft 草图	40 m ² /h
	Production 标准	20 m ² /h
	Quality 精细	12 m ² /h
Cleaning 清洗	清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System
Feed & TakeUp	收放布	Automatic Media Feeding (Standard) & Take up System (Optional)
Rip Software	软件	Main Top (Standard) / Photo Print (Optional)
Connector	接口	USB 3.0
Power	电源	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX
Size 尺寸	Machine 机器	L2960 × W800 × H1270 mm
	Packing 包装	L3210 × W1000 × H740 mm
Weight 重量	Machine 机器	320 KG
	Packing 包装	400 KG

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。