

# *UV Roll To Roll Printer*

3/4 Printheads

White & Varnish

Variable Dot

Negative Pressure System

INDUSTRIAL GRADE






## ● Features 特点



### Different Printheads Available

Epson i3200-U, Ricoh GEN5, Ricoh GEN6 printheads available. Meet the demands of different clients.

爱普生i3200-U, 理光GEN5和GEN6喷头可选。满足不同客户需求。



### Material Tension System

Tension media feeding system is standard equipped to guarantee the high accuracy of material stepping.

张力放布系统。保障高精度步进。



### Negative Pressure System

Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.

配置高级的负压系统。稳定供墨，简化多头设备维护。



### Dual guide rail

Dual guide rail configuration, guarantee the stability of long time running.

双导轨设计，提高设备长时间运行的稳定性



### Anti-collision System

Printer will automatically stop when the carriage hit any unexpected object during working, and support continuing printing from the interruption part, reduce the material waste.

小车遇撞击自动停止，并支持中断处续打，减少意外带来的材料浪费

- ★ Well-designed tension type material feeding and take-up system. Ensure the high accuracy of material stepping.

精心设计的张力收放布系统，精确走步

- ★ Mature time-set stirring system for white ink, effectively decrease the problems caused by white ink precipitation.

成熟的白墨定时搅拌装置，有效防止UV白墨沉淀

- ★ Elegant and sleek appearance design, not only an advanced printing equipment, but also a decoration for the company.

简约大气的外观设计



## ● Specification 参数

Model No.	型号	UR-2000S	UR-2000R	UR-2000Rs	UR-3200Rs
Printing Head	打印喷头	3/4 × Epson i3200-U	3/4 × Ricoh GEN5	3/4 × Ricoh GEN6	3/4 × Ricoh GEN6
Resolution	打印精度	2400 dpi MAX	1200 dpi MAX	1200 dpi MAX	1200 dpi MAX
Media 耗材	Width 耗材宽度	1850 mm MAX	1850 mm MAX	1850 mm MAX	3200 mm MAX
	Type 耗材种类	Canvas, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc. 天花软膜、灯布、车贴、皮革、PET膜、反光膜以及其他众多卷材			
Ink 墨水	Type 墨水类型	UV Ink			
	Color 墨水颜色	CMYK / CMYK+W / CMYK+W+V			
	Curing 墨水固化	High Quality Whater Cooling UV-LED Lamp 水冷UV-LED灯			
Speed 速度	Color Mode 颜色模式	CMYK			
	Draft 草图模式	56 m <sup>2</sup> /h	23 m <sup>2</sup> /h	28 m <sup>2</sup> /h	36 m <sup>2</sup> /h
	Production 标准模式	28 m <sup>2</sup> /h	16 m <sup>2</sup> /h	20 m <sup>2</sup> /h	25.5 m <sup>2</sup> /h
	Quality 精细模式	16 m <sup>2</sup> /h	13 m <sup>2</sup> /h	16 m <sup>2</sup> /h	20.5 m <sup>2</sup> /h
Ink Supply System	供墨系统	Two advanced separate negative pressure systems (One for color and varnish, One for white).			
Cleaning	清洗系统	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头			
Feed & TakeUp	收放布	Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布			
Rip Software	操作软件	Photoprint			
Connector	连接方式	USB 3.0			
Power	电力消耗	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX			
Size 尺寸	Machine 机器尺寸	L3770 x W920 x H1710 mm			
	Packing 包装尺寸	L3870 x W1020 x H1940 mm			
Weight 重量	Machine 机器重量	850 KG			
	Packing 机器重量	1100 KG			

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。