

# Eco Solvent Printer

1.8m DX8/DX5 Printhead

1.8米 爱普生DX8/DX5 户内外写真机

Dual Heads 双喷头

4/6 Color 4/6色写真


Variable Dot 可变墨滴

3-Stage Heater 三段加热

2 Sizes & 3 Print-head Configurations Available  
提供两种尺寸和三种喷头配置



## ● Features 特点




Equipped Epson DX5 or DX8 head  
4 colors and 6 colors models are optional

爱普森DX5和DX8两种喷头可选  
根据你的需求来选择4色或者6色输出



Aluminum Moulding Frame  
Increase machine accuracy and extend machine durability

铝型材开模  
提升机器运行精度并延长使用寿命



Variable Dot Print Technology  
Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes

可变墨滴技术  
使打印画面的颜色过渡更加自然，实现高质量成像



Integrated Take Up System (Optional)  
It offers adjustable roll widths, making it suitable for various sized media rolls and applications

收放布系统  
卷幅宽度可调，适用于众多尺寸的卷材



1 Year or longer Warranty  
The standard warranty period on average is one year. However, SinoColor would like to offer extra warranty period (conditions apply)  
1年或更长的保修期  
儒彩提供超长的保修期（特定前提）

- ★ New look has heavier, larger structure, and wider printing platform  
新造型更加厚重大气，更宽的打印平台
- ★ Aluminous carriage girder ensures high accuracy of carriage movement  
铝制小车梁，精度有保障
- ★ Dual feeding bar for loading heavy media  
双送纸杆，以承受更重的耗材
- ★ Optional infrared heater for drying prints quickly  
选配红外加热装置，画面极速烘干
- ★ Integrated temperature controller  
一体式温控仪



## ● Specification 参数

Model No.	型号	SJ-740C	SJ-740	SJ-740i
Printhead	喷头	2 x Epson DX8	2 x Epson DX5	1 x Epson DX5
Resolution	精度	1440dpi max		
Ink Color	色彩	C M Y K / C M Y K Lc Lm	C M Y K	C M Y K
Media 耗材	Size 尺寸	1.8 meter		
	Types 种类	Flex Banner, Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc. 灯箱布, 车贴, 单透贴, 条幅布, 玻璃贴膜, 网格布等		
Speed 速度	4 Pass 标准	32 sqm/h	30 sqm/h	15 sqm/h
	6 Pass 精细	24 sqm/h	22 sqm/h	11 sqm/h
	8 Pass 照片	18 sqm/h	16 sqm/h	8 sqm/h
Ink Type	墨水	Eco Solvent Ink 弱溶剂墨水		
Ink Droplet	墨滴	1.5-21pl variable 1.5至21皮升可变墨滴		
Cleaning	清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头		
Feed & take up	收放布	Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布		
Environment	环境	Temperature: 20-28 °C, Humidity: 40%-60%		
Rip Software	软件	Maintop/ Photoprint/ Onyx		
Interface	接口	USB2.0		
Power	电源	Machine 50/60HZ, 110 / 220V, 1500W		
Size & Weight	Machine 机器	L3100 x W780 x H1500 mm / 280 KG		
	Packing 包装	L3160 x W960 x H760 mm / 400 KG		

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。