

Direct Textile Printer

for Flag Polyester/Cotton Material

旗帜布/纯棉直喷一体机

Epson Official i3200 Heads

爱普生i3200喷头

1.8m / 3.2m

1.8米 / 3.2米

Integrated Design

一体式设计

Professional

专业





● Features 特点



Epson Official Supplied i3200 Printheads

Two or four heads optional. The speed and quality are guaranteed.


配备Epson原装i3200喷头，速度与品质的保证



Integrated Design

The professional integrated design of printer part and heater part guaranteed the high accuracy of media stepping

一体化的设计，保证了精准的材料步进



Tension Type Media Feeding and Take-up System

Apply to material with different elasticity.


标配材料张力系统，可适应不同弹力的材料稳定走布



Anti-collision system

Printer will automatically stop when the carriage hit any unexpected object. And support to continue printing. Reduce the material waste.

防撞系统，当平台出现异物或者打印材料翘起阻挡小车移动，设备会自动暂停并支持断点续打避免额外的材料浪费



VSDT

Variable Sized Droplet Technology Ensure the smooth color gradations and high quality output.

可变墨滴技术。使打印画面的颜色过渡更自然，实现高质量成像。

● Specification 参数

Model No.		产品型号	FP-740S	FP-740S Pro	FP-1260S	FP-1260S Pro
Printhead 喷头	Type 喷头类型		2 x Epson i3200	4 x Epson i3200	2 x Epson i3200	4 x Epson i3200
	Nozzles 喷嘴数量		3200 Nozzles Per Head			
	Height 高度调节		2-8mm Above Media Adjustable			
Max Printing Width 打印尺寸			1.8m		3.2m	
Resolution (dpi) 打印精度			2400 dpi			
Media Types 适应耗材			Polyester (For flag, display board, light box, etc) 涤纶(用于旗帜、展示板、灯箱等)			
Ink 墨水	Type 墨水类型		Dye Sublimation Ink 热升华墨水			
	Color 墨水颜色		CMYK			
	Droplet 墨滴大小		1.5 – 21pl Variable			
Speed 速度	Draft 标准模式		64 sqm/h	120 sqm/h	80 sqm/h	150 sqm/h
	Production 精细模式		32 sqm/h	60 sqm/h	40 sqm/h	75 sqm/h
	Quality 照片模式		21 sqm/h	40 sqm/h	25 sqm/h	50 sqm/h
Feed & take up 收放布系统			Automatic Tension Type Media Feeding & Take-up System (Standard)			
Cleaning 清洗系统			Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗, 闪喷, 封喷头			
Fabric Drying System 干燥系统			Infrared Heater			
Environment 工作环境			Temperature: 20-28 °C, Humidity: 40%-60%			
Rip Software 图像处理			Maintop/ Photoprint (Optional)			
Control Software 控制软件			SinoColor Print Console			
Interface 输入接口			USB 3.0			
Operation System 操作系统			Windows 7 / XP / 10			
Power 电源消耗			Machine 50 / 60HZ, 110 / 220V			

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。