

# Eco Solvent Printer

3.2m F1080 / i3200 Printhead

3.2米 爱普生 F1080 / i3200 户内外写真机

3 Print-head Configurations Available

提供三种喷头配置

Dual Heads 双喷头

4/6 Color 4/6 色写真

Variable Dot 可变墨滴

3-Stage Heater 三段加热



## ● Features 特点



### Different Printhead Available

Equipped Epson F1080 or i3200 Head. 4 colors and 6 colors models are optional.


根据你的需求来选择4色或者6色输出



### Well Designed Feeding System

Two sets media feeding system are standard equipped. Enable to install both 3.2m heavy banner and 2 rolls small size paper.

配备两套放布系统,方便日常操作



### Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.


标配防撞装置,支持中断处续打



### Branded parts

Greatly increased the lifetime and stability of the machine. For example,Hiwin guide rail,German Igus drag chain, Italian Megadyne belt.

极大提升设备使用寿命和稳定性



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes.

使打印画面的颜色过渡更加自然,实现高质量成像

- ★ New look has heavier, larger structure, and wider printing platform  
新造型更加厚重大气,更宽的打印平台
- ★ Big Functional Control Panel. Adopts the latest program Intelligent Error Auto-Detection boards, it can guide user to find solution very quickly  
超大多功能控制面板,采用智能报错,指导用户快速发现问题
- ★ IGUS Drag Chain from Germany. A guarantee of quality, takes the printer stability to a new level. Effectively protect ink tube and cables  
德国igus拖链,保证高质,有效保护墨管和线路,提高机器稳定性
- ★ LED lamp strip is equipped, users could check out the print result more easily  
配备LED灯条,帮助用户更好的查看打印效果
- ★ Optional infrared heater for drying prints quickly  
选配红外加热装置,画面极速烘干



## ● Specification 参数

Model No.	型号	SJ-1260S	SJ-1260i	SJ-126E
Printhead	喷头	2 x Epson i3200	1 x Epson i3200	2 x Epson F1080
Resolution	精度	2400dpi max	2400dpi max	1440dpi max
Ink Color	色彩	C M Y K	C M Y K	C M Y K / C M Y K Lc Lm
Media 耗材	Size 尺寸	3.2 meter		
	Types 种类	Flex Banner , Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc. 灯箱布, 车贴, 单透贴, 条幅布, 玻璃贴膜, 网格布等		
Speed 速度	Draft 标准	46 sqm/h	28 sqm/h	27 sqm/h
	Production 精细	34 sqm/h	21 sqm/h	20 sqm/h
	Quality 照片	26 sqm/h	16 sqm/h	15 sqm/h
Ink Type	墨水	Eco Solvent Ink		
Ink Droplet	墨滴	1.5-21pl variable		
Cleaning	清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头		
Feed & take up	收放布	Automatic Media Feeding (Standard) & Take up System (Optional)		
Environment	环境	Temperature: 20-28°C, Humidity: 40%-60%		
Rip Software	软件	Maintop (Standard) / Photoprint (Optional)		
Interface	接口	USB 3.0		
Power	电源	Machine 50/60HZ, 110 / 220V, 1500W		
Size & Weight	Machine 机器	L4360 x W780 x H1500 mm / 480 KG		
	Packing 包装	L4610 x W1000 x H740 mm / 640 KG		

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。