

Epson Series UV Roll to Roll Printer

UV卷材打印机 — 高性价比之选

4/5-Color
4/5色写真

Dual Heads
双喷头

Variable Dot
可变墨滴

White Optional
白色可选

Epson Official Supplied i3200-U Printheads

配备爱普生官方原装i3200-U喷头



PRECISIONCORE
PRINTHEAD
i3200-U powered by EPSON

● Features 特点



Epson Official Supplied Printheads
Latest Epson Industrial Printhead i3200-U Equipped. Focus on super fast speed printing.


最新的爱普生i3200-U工业级喷头, 专注高速打印



Water Cooling UV-LED Lamp

It is one of the world's top UV-LED, long lifespan, low heat, and instant on-off


装备世界顶级的UV-LED, 寿命长, 发热低, 即时开关



Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes

使打印画面的颜色过渡更加自然, 实现高质量成像



Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time

标配防撞装置, 支持中断处续打



Integrated Take Up System

It offers adjustable roll widths, making it suitable for various sized media rolls and applications

卷幅宽度可调, 适用于众多尺寸的卷材

- ★ High-density UV curable ink produces rich, vibrant colors on coated or uncoated media
高品质UV固化墨水在涂层或非涂层材料上实现丰富而鲜明的色彩
- ★ Durable, scratch-resistant and virtually odorless, more than three years outdoor durability without lamination
画面持久, 耐刮擦, 无异味, 不覆膜长达三年的户外耐候性
- ★ Branded parts are used for high attrition area. Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt
高损耗处皆使用高等级配件, 极大提升设备使用寿命和稳定性



● Specification 参数

Model No.	型号	UV-740S	
Printing Head	喷头	2 × Epson i3200-U	
Resolution	精度	2400 dpi MAX	
Media 耗材	Width 宽度	1800 mm MAX	
	Type 种类	Canvas, Garment, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc.	
Ink 墨水	Type 类型	UV Ink	
	Color 颜色	C M Y K / C M Y K + W	
	Curing 固化	High Quality Water Cooling UV-LED Lamp	
Speed 速度	Test Color Mode	Color Mode	
	Draft 草图	36 m ² /h	
	Production 标准	26 m ² /h	
	Quality 精细	18 m ² /h	
Cleaning 清洗		Automatic Cleaning, Anti-Clogging Flash Function & Capping System	
Feed & TakeUp 收放布		Automatic Media Feeding (Standard) & Take up System (Optional)	
Rip Software 软件		Main Top(Standard) / Photo Print(Optional)	
Connector 接口		USB 3.0	
Power 电源		AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX	
Size 尺寸	Machine 机器	L2960 × W800 × H1270 mm	
	Packing 包装	L3210 × W1000 × H740 mm	
Weight 重量	Machine 机器	320 KG	
	Packing 包装	400 KG	

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。