

Sublimation Printer

WJ-740S & WJ-1260S

• Features 特点



Epson Official Supplied i3200 Printheads

Two or four heads optional. The speed and quality are guaranteed.

配备Epson原装i3200喷头,速度与品质的保证



Heating and Drying System

Front and middle and rear heating system and front drying fan are standard equipped to help dry the printed material fast.

加热和冷却系统

标配前中后加热系统和前置冷却风扇



Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time

防撞功能

标配防撞装置,支持中断处续打



Branded parts

Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadvne belt.

高损耗处皆使用高等级配件 极大提升设备使用寿命和稳定性



Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes

可变墨滴技术

使打印画面的颜色过渡更加自然, 实现高质量成像

- ★ New look has heavier, larger structure, and wider printing platform 新造型更加厚重大气, 更宽的打印平台
- ★ Aluminous carriage girder ensures high accuracy of carriage movement 铝制小车梁, 精度有保障
- ★ Dual feeding bar for loading heavy media 双送纸杆, 以承受更重的耗材
- ★ Optional infrared heater for drying prints quickly 选配红外加热装置,画面极速烘干
- ★ Integrated temperature controller 一体式温控仪



Sp∈cification 参数

Model No.		코 묵	WJ-740S WJ-1260S
Printhead		喷头	2/3 Epson i3200 (4720) 2/3 Epson i3200 (4720)
Resolution 精度		精度	2400 dpi max
Media 耗材	Size	色彩	1.8 meter
	Types	种类	Heat transfer paper 热转印纸
Speed 速度	Draft	标准	42 sqm/h (Two Heads) 46 sqm/h (Two Heads)
	Production	精细	32 sqm/h (Two Heads) 34 sqm/h (Two Heads)
	Quality	照片	24 sqm/h (Two Heads) 26 sqm/h (Two Heads)
Ink 墨水	Color	色彩	СМҮК
	Туре	墨水	Sublimation Ink
Cleaning 清洗		清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头
Heating System 加热系统		热系统	Pre/Middle/Post Heater Equipped 配备前/中/后三段加热
Drying System 环境		环境	Equipped
Rip Software 软件		软件	MainTop (Standard) / PhotoPrint (Optional)
Interface 接口		接口	USB 3.0
Power 电源		电源	AC 220V, 50/60Hz
Size & Weight	Machine	机器	L3100mm W780mm H1500mm / 280KG
	Packing	包装	L3160mm W960mm H760mm / 400KG L4560mm W960mm H760mm / 640KG