

A3 UV Flatbed Printer

UF-300C

• Features



SinoColor System. Much more professional and more stable than desktop modified printer. Control the color freely.



Media Sensor. Autamatically detect material height.



Well-designed touch screen. Easily Adjust platform position.



Branded circuit breaker to protect the safety of the whole electronic system.



Well-designed adjustable platform. The good smoothness of platform and high accuracy printing are guaranteed.



Low ink alarm, waste ink alarm and water box high temperature alarm are equipped to protect the printer.



| • | | | |
|---------------------------------|---------|--------|--|
| Model No. | | 型号 | UF-300C |
| Printhead | | 打印喷头 | Single Epson DX8 |
| Resolution | | 打印精度 | 1440dpi MAX |
| Max Speed | | 打印速度 | 2 min for full size |
| Print Head Height | | 喷头高度 | 20 cm Max |
| Printing Size | | 打印尺寸 | 30 x 50 cm Max |
| Print Direction | | 打印方向 | Intelligence double sided |
| Print Method | | 打印方法 | micro piezo print technology, intelligence drops transformation technology |
| Height Adjust 高度调节 | | 高度调节 | Electric |
| Distance of Print Head Printing | | | 1-3 mm (1 mm is the best) |
| Ink Color | | 墨水颜色 | CMYK/ CMYK,LC,LM/ CMYK, White |
| Ink Supply System 供墨系统 | | 供墨系统 | CISS |
| Ink Consumption | | 墨水消耗 | 15-20 ml / squre meter |
| Min Ink Drop Size | | 墨滴大小 | < 1.5 PL |
| Interface | | 输入接口 | USB2.0 |
| Rip Software 图像处理 | | 图像处理 | Maintop (Standard)/ Photoprint (Optional)/ Onyx (Optional) |
| Working Environment 工作环境 | | | Temperature 18-30 Celsius, Humidity 30-70 RH, Clean room, Low dust, Less sun light |
| Power 电源输入 | | 电源输入 | AC 110/220 V, 50 Hz/60 Hz |
| Size & Weight | Machine | 机器 | L670mm W565mm H635mm / 90KG |
| | Packing | 包装 | L745mm W745mm H730mm / 100KG |
| Power 电源轴 Size Machine 材 | | 电源输入机器 | AC 110/220 V, 50 Hz/60 Hz L670mm W565mm H635mm / 90KG |

Specifications are subject to change without notice.